

Leica Rugby 600 & 800 Series Comparison



www.sccssurvey.co.uk

ALA MITTELL		III	III	III								I
			100 Cm3	() () () () () () () () () ()			: : : : : : : : : : : : : : : : : : :			(m)	200h	#-250A #-250A #-250A
Instrument	Rugby 610	Rugby 620	Rugby 640	Rugby 640G	Rugby 670	Rugby 680	Rugby 810	Rugby 820	Rugby 830	Rugby 840	Rugby 870	Rugby 880
Туре	Self-levelling horizontal, one button laser	Self-levelling horizontal & manual slope in one axis	Self-levelling horizontal & manual slope in one axis	Self-levelling horizontal & manual slope in one axis	Self levelling horizontal, dial in grade in single axis	Self levelling horizontal, dial in grade in single axis	Self-leveling horizontal, single manual slope (with slope adapter)	Self-levelling horizontal & manual slope in dual axis	Self-levelling horizontal & manual slope in dual axis	Horizontal/ Vertical 90° manual slope in dual axis	Self-levelling Single Grade	Self-levelling Dual Grade
Range	600m	800m	600m	600m	800m	800m	600m	800m	1350m	700m	1100m	1100m
Self-Levelling Accuracy	± 2.2mm @ 30m	± 1.5mm @ 30m	± 1.5mm @ 30m	± 1.5mm @ 30m	± 1.5mm @ 30m	± 1.5mm @ 30m	± 1.5mm @ 30m	± 1.5mm @ 30m	± 1.5mm @ 30m	± 1.5mm @ 30m	± 1.5mm @ 30m	± 1.5mm @ 30m
Rotation Speed	10rps	10rps	0, 2, 5, 10rps	0, 2, 5, 10rps	10rps	10rps	10rps	10rps	10rps	0, 2, 5, 10rps	5, 10rps	5, 10rps
Operating Temperature	-10°C to +50°C	-10°C to +50°C	-10°C to +50°C	-10°C to +50°C	-10°C to +50°C	-10°C to +50°C	-10°C to +50°C	-10°C to +50°C	-10°C to +50°C	-10°C to +50°C	-10°C to +50°C	-10°C to +50°C
Laser Type	(visible) RED	(visible) RED	(visible) RED	(visible) GREEN	(visible) RED	(visible) RED	(visible) RED	(visible) RED	(visible) RED	(visible) RED	(visible) RED	(visible) RED
Battery	Alkaline 60hrs Li-Ion 40 hrs	Alkaline 60hrs Li-lon 40 hrs	Alkaline 60hrs Li-lon 40 hrs	Alkaline 60hrs Li-lon 40 hrs	Alkaline 60hrs Li-Ion 40 hrs	Alkaline 60hrs Li-Ion 40 hrs	Alkaline 60hrs Li-lon 45 hrs	Alkaline 60hrs Li-lon 45 hrs	Alkaline 60hrs Li-lon 45 hrs	Alkaline 60hrs Li-lon 45 hrs	Alkaline 60hrs Li-lon 45 hrs	Alkaline 60hrs Li-lon 45 hrs
Protection Class	IP67	IP67	IP67	IP67	IP67	IP67	IP68	IP68	IP68	IP68	IP68	IP68
Remote												
Smart Targeting		3.		Ere .			Smart Targeting	Smart Targeting	Smart Targeting	Smart Targeting	Smart Targeting	Smart Targeting
Smart Lock		14						⊕	•		@	(a)
Machine Control												
Horizontal/Vertical			- 1		- 1							
Grade Capability				ey.								